

HD-AQUA-PUR PARKETTSIEGEL 72x-0001

Product Description

HD-AQUA-PUR PARKETTSIEGEL is a water-based single component coating for stairs which can be used as primer and top coat. It is environmentally-friendly and virtually odourless finish for coating of wooden floors and solid wood stairs.

Has virtually the same features of a 2C polyurethane coating after hardening. Suited for all wood types

Process Description

Stairs and Floors - Natural Beech Semi-Matt

1. Priming

1 x 80 g / m², priming with HD AQUA-PUR- PARKETTSIEGEL 72X-0001. Drying at least 2 hours at room temperature. Coat sanding with sanding paper, grain 280-320

2. 1st Coat

1 x 80-120 g / m²,
HD AQUA-PUR- PARKETTSIEGEL 72X-0001, after drying min 2-4 hours (best overnight), sand with sanding paper , grain 240 - 320.

3. 2nd Coat

1 x 80-120 g / m² HD AQUA-PUR- PARKETTSIEGEL 72X-0001

Optional: To increase scratch resistance of this product add 5% of HE/760-0005 (in ratio 20:1 lacquer/hardener).

Indication

All drying times given are based on a room temperature of 20°C at a relative air humidity of 65%.

Ensure good ventilation.

Water-based coatings should not get into contact with solvents!

Stir Well before use.
Trials should be carried out.

Standards

Corresponds to the VOC regulation

DIN 68861 – part 1 - chemical resistance

DIN EN 71 – 3 - Safety of Toys

Composition free of:

Poisonous heavy metals, halogenated hydrocarbons (CKW, FCKW), polychlorinated bi- and terphenyls (PCB+PCT), pentachlorophenol (PCP) and formaldehyde.



Processing

Applied with cup gun, brush or roller

Nozzle size 2,0-2,5, spray pressure 2,5-3,0 bar

Tip: Water-based coatings are only to be processed at 18-20 °C and air humidity of 65%

Technical Data

Viscosity: 25 sec. in DIN4 cup
Drying: After 15-30 min dust dry
Can be sanded after 2 hours
Storage after 12 hours

Coating Rate: 80 - 100g/m

Ordering Information

Order Number:

72x-0001-25KI	25kg packaging
72x-0001-10KI	10kg packaging
72x-0001-5KI	5kg packaging

Gloss Levels:

2 - matt	3 - semi-matt
5 - satin gloss	8 - high gloss

Shelf Life:

Unopened at least 6 months at room temperature (max. 30°C).

Warning - FROST SENSITIVE !!!